



# Technical Datasheet

Product Name	Product Code
<b>TM TOP GR 9B</b>	A Y5 115

**Texbond**  
nonwovens

material	laminate structure	type	colour
polypropylene	S/F/S	breathable	white/grey

## Properties

Properties	Dir.	Unit	Method	Typical value
Mass per unit area	-	g/m <sup>2</sup>	EN 1849-2	<b>115</b>
Tensile strength	MD	N/5cm	EN 12311-1*	<b>200</b>
Tensile strength	CD	N/5cm	EN 12311-1*	<b>130</b>
Elongation at break	MD	%	EN 12311-1*	<b>60</b>
Elongation at break	CD	%	EN 12311-1*	<b>70</b>
Tear strength (nail shank)	MD	N	EN 12310-1*	<b>105</b>
Tear strength (nail shank)	CD	N	EN 12310-1*	<b>125</b>
Water penetration resist.	-	cm	EN 20811	<b>&gt; 300</b>
Sd-value	-	m	EN ISO 12572	<b>0,04</b>
UV stability	-	months	-	<b>4</b>
Temperature resistance	-	°C	-	<b>- 40 / + 80</b>

Folded sample as per EN13859-1  
BL3

The figures provided in this datasheet are consistent with the current state of our knowledge, and are intended to provide general information on our product and its applications. They are not a guarantee of any specific product attribute or the suitability of the product for a specific application.

issue date:12/12/07

