



Texbond
nonwovens

Technical Datasheet	
product	ULTRATEX
type	B

	weight	tensile strength		elongation at break		tear strength	
method	TEXBOND	EDANA 20.2-89		EDANA 20.2-89		EDANA 70.4-99	
unit	g/m ²	N/5cm	N/5cm	%	%	N	N
direction	-	MD	CD	MD	CD	MD	CD

typical values*	14	23	21	50	55	11	11
	15	24	22	51	56	12	12
	16	25	23	52	57	13	13
	17	26	24	53	58	14	14
	18	27	25	54	59	16	16
	20	30	28	55	60	18	18
	25	40	38	57	63	23	23
	30	50	45	60	65	32	32
	35	64	58	64	67	44	43
	40	72	67	68	70	57	54
	50	90	85	70	72	70	68
	60	112	100	72	73	82	79
	70	125	117	69	70	94	90
	80	135	128	67	68	105	100
	90	145	138	64	65	117	112
100	155	143	64	65	129	124	
110	162	150	64	65	144	136	

* actual values depend on the colour, additives and PP resin type

The figures provided in this datasheet are consistent with the current state of our knowledge, and are intended to provide general information on our product and its applications. They are not a guarantee of any specific product attribute or the suitability of the product for a specific application.